

TECHNICAL INFORMATION

Hardwood Floor Cleaner



Ready to use, pH neutral cleaner. Quick cleaning, dries without streaks

- Very high yield concentrated cleaning solution
- Hygienic
- Dries without streaks
- Does not leave any residue
- Environmentally friendly

Recommended use:

Cleaning of cork and wood floors and other hard and elastic floors as well as doors or other water-proof hard surfaces.

Technical Data

Art.-no.
10176

Item-#:
LO-MA-005



1 Qt.



12



576

pH 7,7

Contents METHYLISOTHIAZOLINONE, BENZISOTHIAZOLINONE, perfumes

Storage and transportation Shelf life: 36 months in unopened containers. Store and transport between 41°F to 77°F. KEEP FROM FREEZING.

Application

- BEFORE USING, READ AND UNDERSTAND ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our WAKOL Technical Service at 1-800.230.6456.
- Shake material well before use.

Application Tool

Micro-fiber mop

Coverage

Up to 5.000 square feet per 1 quart bottle.

TECHNICAL INFORMATION

Hardwood FloorCleaner



Application

Cleaning Process:

- Moist the area you like to clean with the Hardwood FloorCleaner.
- Use a Mop to wipe the area dry and clean.

Refill:

Pour 25% (1/4) of a 8.45 fl.oz. Refill bottle (250ml) into the empty Hardwood Floor Cleaner Spray bottle and fill up with clean water.

TECHNICAL INFORMATION

Hardwood FloorCleaner



General guidelines

Cleaning of tools: Clean tools and equipment immediately with water.

Cure Time: The stated drying and cure times are based on ideal conditions (68°F, 65% rH) at the recommended application rates. Recommended conditions are 50°F-77°F/40-75%rH). Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. The floor can be lightly used 24 hours after application, but is still susceptible to scuffing or marring at this time. Full curing is achieved after 5 days. Do not use safety covers on floor, do not replace carpets or rugs and also do not clean floors with a damp cloth before the final hardness has been reached.

Safety Precautions: Even when working with low-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink or smoke in working areas. Wear suitable safety gloves. Make sure working areas are ventilated sufficiently. Clean left-overs off of hands. Change soiled clothes. Ventilate working rooms during working and drying time avoiding draft.

First Aid: If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If breathing is difficult or other respiratory complaints, get medical attention. In case of contact, immediately flush eyes or skin with plenty of water. Do not use solvents or thinners. Remove contaminated clothing or shoes. For eye contact, rinse opened eye for several minutes under running water. Call a physician if irritation occurs.

WARNING! If you scrape, sand or remove old paint from wooden floors, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Special Information The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.