



As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years of experience. This product has had extensive tests carried out.

### Produced by Debal Coatings NV

Industrieweg 29 - 8800 Beveren-Roeselare  
Belgium  
tel. +32 (0) 51 30 11 40  
fax +32 (0) 51 31 26 48  
ciranova@ciranova.be

## TECHNICAL DATA SHEET

# Vica Maintenance Oil

### PRODUCT DESCRIPTION

Universal maintenance system for oiled wooden floors. For the maintenance of floors treated with flooring oil and UV-oil. Different colours available.

### TECHNICAL DATA

FYSISCHE TOESTAND	fluid
APPEARANCE	dark yellow
SOLID CONTENT	26%

### USE

To maintain floors treated with Hardwaxoil and UV-oil.

### PREPARATION

With Hardwaxoil treated wood: remove soap rests with pure water and let dry.

### USER TIPS

Apply a thin layer of Vica Maintenance Oil and let impregnate for a few minutes. Whip of white a clean cloth. Polish the oil well dry to avoid sticking.



### DRYING TIMES

Do not charge the first 12 hours!  
The optimal hardness is reached after 48 hours. Don't use any water or maintenance products during this period.



### APPLYING QUANTITY

50 m<sup>2</sup>/l for the maintenance of already treated wooden floors.

### AFTER TREATMENT

It's recommended to treat the floor each year with Vica Maintenance Oil.

### SPECIAL QUALITIES

Used cloths need to be thrown into water after use, to decrease flamability. The presence of linseed oil in the system causes this measure.