### Product Spec Sheet

Installation Guide Hardwax Oil Maintenance Guide Polyurethane Maintenance Guide Warranty Information

# WEST WOOD ARCHITECTURAL SURFACES

## SERRATED IVORY Winter Beach Color Collection

Serrated lvory features a natural hardwax oil finish with a band-sawn texture. The textures gives a mix of character and appeal, cool but gentle.

#### Specification Options for White Oak

Other species are available (see below) but may have different specifications to consider.

#### Design Elements

SPECIES	 	White Oak (American, European or French), Red Oak, Walnut, Maple, Hickory, Pine & other preferred species
PATTERNS	 	Bordeaux, Chevron, Haddon Hall, Herringbone, Marie Antoinette, Versailles or Custom
CUTS OF WOOD	 	Plain Sawn, Live Sawn, Rift Sawn, Quarter Sawn & R&Q Sawn
GRADE QUALITY		Perfect, Clear, Select & Better, Character, Rustic & Prime
TEXTURES	 	Smooth, Wire Brushed, Hand Scraped, Band Sawn, Distressed & French Bleed
PRE-TREATMENTS & STAINS	   	Bleach & Water Treatments, Water-Based Stains, Aniline Dyes, Cerused, Fuming & Other Specialty Branded Pre-Treatments
TOP COATS	 	Hardwax Oil, Polyurethane (Oil- & Water-Based), Wax, Tung Oil & Moisture Cure & Conversion Varnish



#### Production Elements

CONSTRUCTION	Engineered or Solidd
ENGINEERED WIDTHS	5- $\frac{1}{2}$ ", 6", 7", 8", 9- $\frac{1}{2}$ ", 10- $\frac{1}{4}$ " & 12" options with a Baltic Birch core that contains between 8 & 11 plies. Or 11- $\frac{1}{2}$ ", 13- $\frac{1}{2}$ ", 15- $\frac{1}{2}$ " & 17- $\frac{3}{4}$ " using balanced Oak (Oak top and bottom) with 8 plies.
SOLID WIDTHS	4-¾"-8", with custom widths available upon request
ENGINEERED THICKNESSES	1⁄2″, 5⁄8″ & 3⁄4″
SOLID THICKNESS	3/4"
ENGINEERED LENGTHS	2'-8', 2'-10', 4'-8', 4'-10', 6'-10' & 6'-14-½', depending upon the material selected
SOLID LENGTHS	1'-7', 1'-8', 2'-8', 2'-10', 3'-10', 3'-12', 6'-10', 6'-12', with possible longer options
ENGINEERED WEAR LAYERS	3mm, 4mm, 5mm & 6mm options, based upon material selected