Product Spec Sheet

Installation Guide Hardwax Oil Maintenance Guide Polyurethane Maintenance Guide Warranty Information

WEST WOOD ARCHITECTURAL SURFACES

SUNSTONE Natural Vintage Color Collection

Shades of brown, combined with a light grain throughout, show some of the natural colors of stone as the sun shines against it.

Specification Options for White Oak

Other species are available (see below) but may have different specifications to consider.

Design Elements

SPECIES	 	White Oak (American, European or French), Red Oak, Walnut, Maple, Hickory, Pine & other preferred species
PATTERNS		Bordeaux, Chevron, Haddon Hall, Herringbone, Marie Antoinette, Versailles or Custom
CUTS OF WOOD	 	Plain Sawn, Live Sawn, Rift Sawn, Quarter Sawn & R&Q Sawn
GRADE QUALITY		Perfect, Clear, Select & Better, Character, Rustic & Prime
TEXTURES	 	Smooth, Wire Brushed, Hand Scraped, Band Sawn, Distressed & French Bleed
PRE-TREATMENTS & STAINS	 	Bleach & Water Treatments, Water-Based Stains, Aniline Dyes, Cerused, Fuming & Other Specialty Branded Pre-Treatments
TOP COATS	 	Hardwax Oil, Polyurethane (Oil- & Water-Based), Wax, Tung Oil & Moisture Cure & Conversion Varnish



Production Elements

CONSTRUCTION	Engineered or Solidd
ENGINEERED WIDTHS	 5-½", 6", 7", 8", 9-½", 10-¼" & 12" options with a Baltic Birch core that contains between 8 & 11 plies. Or 11-½", 13-½", 15-½" & 17-¾" using balanced Oak (Oak top and bottom) with 8 plies.
SOLID WIDTHS	4-¾"-8", with custom widths available upon request
ENGINEERED	½", 5%" & 3/4"
THICKNESSES	
SOLID	3/4″
THICKNESS	
ENGINEERED	2'-8', 2'-10', 4'-8', 4'-10', 6'-10' & 6'-14-1⁄2',
LENGTHS	depending upon the material selected
SOLID LENGTHS	1'-7', 1'-8', 2'-8', 2'-10', 3'-10', 3'-12', 6'-10', 6'-12', with possible longer options
ENGINEERED	3mm, 4mm, 5mm & 6mm options,
WEAR LAYERS	based upon material selected