### Product Spec Sheet

Installation Guide Hardwax Oil Maintenance Guide Polyurethane Maintenance Guide Warranty Information

# WEST WOOD ARCHITECTURAL SURFACES

## TRENCH Blackish Color Collection

Trench, with shades of deep black reflecting serrations of navy, offers a unique and contemporary design.



#### Specification Options for White Oak

Other species are available (see below) but may have different specifications to consider.

#### Design Elements

SPECIES		White Oak (American, European or French), Red Oak, Walnut, Maple, Hickory, Pine & other preferred species
PATTERNS	 	Bordeaux, Chevron, Haddon Hall, Herringbone, Marie Antoinette, Versailles or Custom
CUTS OF WOOD		Plain Sawn, Live Sawn, Rift Sawn, Quarter Sawn & R&Q Sawn
GRADE QUALITY		Perfect, Clear, Select & Better, Character, Rustic & Prime
TEXTURES		Smooth, Wire Brushed, Hand Scraped, Band Sawn, Distressed & French Bleed
PRE-TREATMENTS & STAINS		Bleach & Water Treatments, Water-Based Stains, Aniline Dyes, Cerused, Fuming & Other Specialty Branded Pre-Treatments
TOP COATS		Hardwax Oil, Polyurethane (Oil- & Water-Based), Wax, Tung Oil & Moisture Cure & Conversion Varnish

#### Production Elements

CONSTRUCTION	Engineered or Solidd
ENGINEERED WIDTHS	<ul> <li>5-½", 6", 7", 8", 9-½", 10-¼" &amp; 12" options with</li> <li>a Baltic Birch core that contains between 8 &amp; 11</li> <li>plies. Or 11-½", 13-½", 15-½" &amp; 17-¾" using</li> <li>balanced Oak (Oak top and bottom) with 8 plies.</li> </ul>
SOLID WIDTHS	4-¾"-8",   with custom widths available upon request
ENGINEERED	½", 5%" & 3/4"
THICKNESSES	
SOLID	3/4"
THICKNESS	
ENGINEERED	2'-8', 2'-10', 4'-8', 4'-10', 6'-10' & 6'-14-1⁄2',
LENGTHS	depending upon the material selected
SOLID LENGTHS	1'-7', 1'-8', 2'-8', 2'-10', 3'-10', 3'-12', 6'-10', 6'-12',   with possible longer options
ENGINEERED	3mm, 4mm, 5mm & 6mm options,
WEAR LAYERS	based upon material selected